



# SOFAR 1.1k~3.3kTL-G3

1100/1600/2200/2700/3000/3300

## Single-Phase

## Single-MPPT

1.4

1.4 DC overload



IP65 ingress protection

97.7%

Max. efficiency up to 97.7%



Light weight, quick and easy to install

0

Built-in zero export function



Smart monitoring, RS485, Wifi/Ethernet/GPRS(optional)

# Datasheet

SOFAR  
1100TL-G3

SOFAR  
1600TL-G3

SOFAR  
2200TL-G3

SOFAR  
2700TL-G3

SOFAR  
3000TL-G3

SOFAR  
3300TL-G3

## Input (DC)

Recommended Max. PV input power	1500Wp	2200Wp	3000Wp	3700Wp	4100Wp	4500Wp
Max. Input voltage	500V	500V	500V	550V	550V	550V
Start-up voltage	70V					
Rated input voltage	360V					
MPPT operating voltage range	50-500V	50-500V	50-500V	50-550V	50-550V	50-550V
Full power MPPT voltage range	110-450V	150-450V	200-450V	250-500V	275-500V	300-500V
Max. Input current MPPT	12A					
Maximum DC input short circuit current per MPPT	15A					
Number of MPPT/ String per MPPT	1/1					
Input terminal type	MC4/H4					

## Output (AC)

Rated power	1100W	1600W	2200W	2700W	3000W	3300W
Max. AC power	1100VA	1600VA	2200VA	2700VA	3000VA	3300VA
Rated Output current	4.8A	7A	9.6A	11.8A	13A	14.3A
Max. Output current	5.3A	7.7A	10.6A	13A	14.5A	16A
Nominal grid voltage	L/N/PE, 220Vac, 230Vac, 240Vac					
Grid voltage range	180Vac-276Vac (According to local standard)					
Nominal frequency	50Hz/60Hz					
Grid frequency range	45~55Hz/54~66Hz (According to local standard)					
THDi	<3%					
Power factor	1 default (adjustable +/-0.8)					

## Efficiency

Max. Efficiency	97.5%	97.5%	97.5%	97.7%	97.7%	97.7%
European weighted efficiency	96.9%	96.9%	96.9%	97.2%	97.2%	97.2%

## Protection

Anti-Islanding protection	Yes
DC reverse polarity protection	Yes
Over temp protection	Yes
Leakage current protection	Yes
Over voltage protection	Yes
Over current protection	Yes
Earth fault protection	Yes
SPD	MOV: Type III standard

## Communication

Standard communication mode	RS485, WiFi/GPRS/Ethernet(optional), USB
-----------------------------	--

## General Data

Topology	Transformerless					
Ambient temperature range	-30°C~+60°C					
Allowable relative humidity range	0~100%					
Noise	<25dB					
DC switch	optional					
Cooling	Natural convection					
Max. Operating altitude	2000m					
Dimension[mm]	303*260.5*118	303*260.5*118	303*260.5*118	321*260.5*131.5	321*260.5*131.5	321*260.5*131.5
Support bracket	Wall-mounted					
Weight	5.5kg	5.5kg	5.5kg	6.3kg	6.3kg	6.3kg
Display	LCD+LED					
Degree of protection	IP65					
Warranty	5 years/ 7 years/ 10 years					

## Standard

EMC	EN 61000-6-1, EN 61000-6-3, EN 61000-3-2, EN 61000-3-3					
Safety standards	IEC 62116, IEC 61727, IEC 61683, IEC 60068(1,2,14,30), IEC 62109-1/2					
Grid standards	AS 4777, VDE V 0124-100, VDE V 0126-1-1, VDE-AR-N 4105, G83/2, C10/11, RD 1699					